FEB-24-2005 14:36 FOXCONN 408 919 8353 P.03

Appl. No. 10/600,517 Amdt. Dated Feb. 24, 2005

Reply to Office Action of January 14, 20045

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

Claim 1 (currently amended): A cable assembly comprising:

an insulating housing defining a plurality of channels;

a cover assembled to the insulating housing and latchably engaged with the

insulating housing; and

a plurality of circuit modules juxtaposed in the housing, each circuit module

comprising a circuit board received in a corresponding channel of the housing, a

plurality of coaxial cables connecting to the circuit board, a cable clamp binding

the cables together, and a grounding plate, each coaxial cable being electrically

connected with the grounding plate; wherein

the each circuit board defines a plurality of cavities and the grounding plate

has a plurality of tabs retained in corresponding cavities of the circuit board.

Claim 2 (original): The cable assembly as described in claim 1, wherein each

coaxial cable comprises a conductive core and a metal braid surrounding the

conductive core, and wherein the conductive core is soldered to the circuit board.

and the metal braid is soldered with the grounding plate.

Claim 3 (canceled)

Page 2 of 6

Appl. No. 10/600,517 Amdt. Dated Feb. 24, 2005 Reply to Office Action of January 14, 20045

Claim 4 (original): The cable assembly as described in claim 1, wherein each cable clamp comprises a first and a second stamped metallic sections clamping the coaxial cables from opposite sides.

Claim 5 (original): The cable assembly as described in claim 4, wherein the first section defines a plurality of rooms and the coaxial cables are depressed into the rooms by the second section.

Claim 6 (original): The cable assembly as described in claim 1, further comprising a fastening element, and wherein each cable clamp defines at least one through hole for insertion of the fastening element.

Claim 7 (original): A cable assembly comprising:

an insulating housing comprising a plurality of channels and an aperture extending along a direction perpendicular to the channels;

a plurality of circuit modules each comprising a circuit board being retained in a corresponding channel of the housing and defining therethrough a hole aligned with the aperture of the housing, a plurality of cables electrically connecting to one side of the circuit board, and a grounding plate attached to an opposite side of the circuit board, each cable comprising a metal braid electrically soldered with grounding plate;

a cover comprising first and second halves jointed together and being attached to the housing, the cover defining a bore extending through the first and second halves; and

first and second fastening elements respectively inserted into the holes of the

Appl. No. 10/600,517 Amdt. Dated Feb. 24, 2005 Reply to Office Action of January 14, 20045

circuit boards through the aperture of the housing and the bore of the cover for retaining the circuit modules relative to the housing.

Claim 8 (previously presented): The cable assembly as described in claim 7, wherein each circuit board defines a plurality of cavities and the grounding plate has a plurality of tabs retained in corresponding cavities of the circuit board.

Claim 9 (original): The cable assembly as described in claim 8, wherein each circuit module further comprises a cable clamp binding the cables together.

Claim 10 (original): The cable assembly as described in claim 9, further comprising a third fastening element, and wherein the cable clamp defines a through hole therein for providing the third fastening element inserting thereinto.

Claim 11 (previously presented): A cable assembly comprising: an insulative housing;

a plurality of juxtaposed printed circuit boards disposed in the housing, each of said printed circuit boards defining opposite first and second surfaces and a cutout in a rear edge section thereof;

a plurality of juxtaposed coaxial cables located along said rear edge section of each of said printed circuit boards, each of said cables extending along a first direction parallel to the corresponding printed circuit board while substantially perpendicular to a rear edge of the corresponding printed circuit board; and

a grounding plate fixedly positioned on the second surface of said each of the printed circuit boards around the corresponding rear edge section,

said each of said cables defining an inner conductor, an inner insulator, a

Appl. No. 10/600,517 Amdt. Dated Feb. 24, 2005 Reply to Office Action of January 14, 20045

metallic braiding and an outer insulator concentrically arranged with one another in outward sequence, the inner conductor soldered on the first surface while the braiding located in said cutout of a corresponding printed circuit board and mechanically and electrically connected to the grounding plate.

Claim 12 (previously presented): The assembly as described in claim 11, wherein the braiding of each of said cables engages the grounding plate located beside said cutout in a second direction perpendicular to said first direction.

Claim 13 (previously presented): The cable assembly as claimed in claim 1, wherein the cover comprises a first and a second halves assembled to each other in a direction perpendicular to an extending direction of the coaxial cables.

Claim 14 (previously presented): The cable assembly as claimed in claim 13, wherein the first and the second halves of the cover latch with the insulating housing in the extending direction of the coaxial cables.

Claim 15 (previously presented): The cable assembly as claimed in claim 1, wherein the cover is made of insulative material.